



modello model	Ø A
PST63P	62 mm
PST80P	80 mm
PST100P	99,4 mm

guaine standard standard pockets	L
1/2 x 5 cm	50 mm
1/2 x 10 cm	105 mm

Radial thermometer with stem and plastic casing (painted steel only for Ø 100); not intended for specific uses but particularly suitable for heating systems.

CASING: shockproof black ABS (painted steel only Ø 100). The diameters available are listed in the table.

TRANSPARENT: unbreakable methacrylate.

DIAL: printed with UV inks on pre-painted aluminium. Customer's logo or special graphics on request.

STANDARD GRADUATIONS: -30/+50 0/60 0/120 °C. Other graduations on request, including graduations in °F or with double scale °C/°F.

MECHANISM: sensitive precision element with liquid expansion.

STEM: turned brass. Standard rated length (C) cm 5 and 10. Different stem lengths may be supplied on request.

SHEATH: The thermometer is usually supplied complete with a sheath. The sheath may be made of a bar of turned brass (rated length 5 cm) or with a turned brass coupling and a tubular copper stem (rated length 10 cm). Sheaths with different measurements, threads and characteristics may be supplied on request.

LANTERN SPRING: burnished steel. Its purpose is to hold the thermometer stem inside the sheath, or other housing, by friction.

NOTE: the standard models are available from the SERVICE (please click on SERVICE LINE).